



TITAN

Hose Reel Selection Guide

- U-Channel Frame Full Frame Manual Rewind
- Full Frame Manual Rewind With Pin-Lock
- 12 Volt Electric With Switch and Solenoid



Hose Diameter (in)							Inlet X Outlet NPT	Aluminum Frame Reel Models			Stainless Steel Reel Models			Spool:	
I.D. (in)	¼	3/8	½	5/8	¾	1"		U-CHAN.	FULL FRAME	ELECT REWIND	U-CHAN.	FULL FRAME	ELECT REWIND	Width (in)	Dia. (in)
O.D. (in)	5/8	3/4	7/8	1"	1-9/32	1-9/16									

HOSE LENGTH IN FEET		200	150	100	75	150	90	1/2"	4806H	4306H		5406	5506		6	6
		425	300	200	150	225	150	1/2"	4812H	4312H	4312E	5412	5512	5512E	12	6
		625	450	325	225	300	225	1/2"	4818H	4318H	4318E	5418	5518	5518E	18	6
			550	400	300	375	300	1/2"		4322H	4322E		5522	5522E	22	6
				500	375	450	375	1/2"		4328H	4328E		5528	5528E	28	6
						150	90	1"		4012-6	4012-6E				12	6
						225	150	1"		4018-6	4018-6E				18	6
						300	180	1"		4022-6	4022-6E	5022-6	5022-6E	22	6	6
						375	230	1"		4028-6	4028-6E				28	6
						60	42	1"		4012-8	4012-8E				12	8
						110	55	1"		4018-8	4018-8E				18	8
						150	75	1"		4022-8	4022-8E				22	8
						185	90	1"		4028-8	4028-8E				28	8

CALL FOR TEMPERATURE ABOVE 140° F.
 800 519-9279 727 562-5488 727 449-1559

STYLE:	MATERIALS OF CONSTRUCTION:				
	MANIFOLD	DISKS	SPOOL	HARDWARE & TIERODS	SWIVEL
ALUMINUM FRAME REELS MODELS 48XX, 43XX, 40XX	BLACK IRON	ALUM	PVC	STAINLESS STEEL	SEE SWIVELS
STAINLESS STEEL REELS MODELS 54XX, 55XX	STAINLESS STEEL	STAINLESS STEEL	PVC	STAINLESS STEEL	SEE SWIVELS